



Amarr® Commercial Sectional Doors

- 
- 4 ALUMINUM MULTIVIEW DOOR
 - 6 ALUMINUM FULL VIEW DOORS
 - 8 POLYURETHANE INSULATED STEEL DOORS
 - 12 POLYSTYRENE INSULATED STEEL DOORS
 - 14 RIBBED PANEL STEEL DOORS
 - 16 SUPERFLEX IMPACT SECTIONS
 - 17 WIND LOAD & TRACK OPTIONS
 - 18 PRODUCT SPECIFICATIONS & AMARR COLOR ZONE

INDUSTRIA STRENGTH



Why Choose Amarr Commercial Sectional Doors?

PRODUCTS

Entrematic offers a wide range of high-quality, LEED qualified, sustainable products to meet the needs of architects, specifiers, and building professionals.



Amarr doors are designed and tested in our state-of-the-art research facility and manufactured to meet or exceed industry standards.

Our wind load approved and hurricane rated commercial doors meet or exceed building code requirements. See page 15 for more information.

SERVICE

Our Door Centers, strategically located throughout North America, supply our products to over 3,000 professional door dealers and installers.

SUPPORT

Ace Commercial Experts (ACE) provide dealer support for our commercial products, programs, systems, and training. Contact 866.366.4814 or ace@entrematic.com.

Free AIA accredited continuing education courses.

ARCHITECT RESOURCES

architects.amarr.com

- Product Brochures
- 3-Part Specifications
- CAD/BIM Details
- SketchUp Models
- Installation Instructions
- LEED Documentation
- Lunch & Learn Education

MasterSpec®
masterspec.com

eSPECS™
link.sync.integrate
e-specs.com

speclink-e
bsdsoftlink.com

@AEC DAILY
COURSES FOR AIA CREDIT
aeedaily.com

CADdetails
caddetails.com

3D Warehouse
3dwarehouse.sketchup.com

Sweets™
sweets.construction.com

4specs.com
4specs.com

ARCAT
arcat.com



Aluminum MultiView Doors


Amarr 3582 MultiView Aluminum door

Amarr 3582 Aluminum MultiView doors make a unique design statement with the widest single piece of glass that specifications, safety, and reliability standards allow. Constructed of 2" thick extruded aluminum rails and stiles, these doors are built to last. The ClearView Aluminum Strut System provides strength and durability without restricting the viewing area. With a wide selection of glass, acrylic and polycarbonate glazing options, in more than two dozen paint and anodize finishes, the Amarr 3582 is a distinctive choice for any building where style and functionality are important.



CONSTRUCTION

SINGLE-LAYER Aluminum



- 2" thick extruded aluminum rails & stiles
- Tongue and groove section joint with leading-edge bulb seal and bottom weather seal provide greater protection from the elements
- Equal glass heights in all sections of a door
- Glass expands up to 8'2" wide

SPECIFICATIONS

	Modern Amarr 3582
MATERIAL	Aluminum
CONSTRUCTION LAYERS	Single
DOOR THICKNESS	2" [5.1cm]
SECTION HEIGHTS ¹	Varies by door height
MINIMUM DOOR WIDTH	2' 0"
MAXIMUM DOOR WIDTH	20' 2" [in 1" increments]
MINIMUM DOOR HEIGHT ¹	6' 0"
MAXIMUM DOOR HEIGHT ¹	20' 1"
CLEARVIEW STRUT SYSTEM	Only required for doors ≥ 16'
WIND LOAD ² AVAILABLE	NA
FINISH WARRANTY ³	5 Years
WORKMANSHIP/HARDWARE WARRANTY ³	1 Year
GLASS WARRANTY ³	1 Year

¹ For complete door height configuration chart visit amarr.com or contact your local Amarr dealer.
² It is your responsibility to make sure your garage door meets local building codes.
³ For complete warranty details, visit amarr.com or contact your local Amarr dealer.

GLAZING OPTIONS

	Single Pane											Insulated	
	Tempered				Lami- nated	Polycarbonate			Acrylic			Tempered	
	3/16"	3/16" Low-E	1/4"	1/4" Low-E		Single 1/8"	Single 1/4"	Tri-Wall 5/8"	1/8"	1/4"	1/2"	1/2"	1/2" Low-E
CLEAR	STD	•	•	•		•	•	•	•	•	•	•	•
OBSCURE	•												
GRAY	•											•	•
BRONZE	•							•				•	•
GREEN	•											•	•
FROST	•		•					•				•	
SNOW					•			•					
WHITEOUT					•								
BLACK ICE					•								



Amarr 3582 with Champagne Pearl finish and Clear glass



Amarr 3582 with Champagne Pearl (PVDF) frame and Clear glass.

DOOR CONFIGURATIONS

For Single Pane Glazing

Door Width	# Center Stiles	# Windows/Section
Up to 8' 2"	0	2
8' 3" - 16' 2"	1	4
16' 3" - 20' 2"	2	6


Up to 8' 2" Wide - 1 Panel



8' 3"-16' 2" Wide - 2 Panels



16' 3"-20' 2" Wide - 3 Panels



For Insulated Glazing

Door Width	# Center Stiles	# Windows/Section
Up to 10' 2"	1	4
10' 3" - 16' 2"	2	6
16' 3" - 20' 2"	3	8

Up to 10' 2" Wide - 2 Panels



10' 3"-16' 2" Wide - 3 Panels



16' 3"-20' 2" Wide - 4 Panels



COLORS

Actual color may vary from samples shown.

In Stock

ANODIZE



CLEAR (AN)




DARK BRONZE (AD)



BLACK (BA)

PAINT



WHITE Powder Coat (WH)

Special Order

ANODIZE

Longer lead time and price upcharge apply.



CHAMPAGNE (AH)



COPPER (AC)



MEDIUM BRONZE (AM)

PAINT

PVDF (Kynar®) & Powder Coat

Longer lead time and price upcharge apply.



WHITE (PVDF)




BONE WHITE



IVORY



SANDSTONE



BURNT SUN



SIERRA TAN



BEIGE



LIGHT SEAWOLF BEIGE



DOVE GRAY



SLATE GRAY



CHARCOAL GRAY



PATINA GREEN



DARK IVY



HARTFORD GREEN



MILITARY BLUE



INTERSTATE BLUE



COLONIAL RED



BOYSENBERRY



SAGE BROWN



QUAKER BRONZE



SUPER BLACK




CARNIVAL RED II†



CLASSIC COPPER†



CHAMPAGNE PEARL†



PEWTER†



SILVER†

†PVDF only.



	PVDF (Kynar®)	Powder Coat
FADE RESISTANT	++	+
CORROSION RESISTANT	++	+
UV RESISTANT	++	+
ABRASION RESISTANT	+	++
STANDARD COLORS	26	21
RAL/CUSTOM COLORS PRICE UPCHARGE	\$	\$\$
TOUCH-UP PAINT	Included	NOT included

Aluminum Full View Doors

Amarr 3552

Heavy-Duty Aluminum door

Amarr 3502


Medium-Duty Aluminum door

Amarr Aluminum Full View doors can be fitted with a variety of full view glass options, solid aluminum, perforated or louvered ventilation panels. Full View panels can also be used in Amarr sectional steel doors. Perfect for service stations, car washes, fire houses, restaurants, and sports complexes; our aluminum doors create a clean style for any facility.



CONSTRUCTION

SINGLE-LAYER Aluminum



- 2" thick extruded commercial-grade aluminum frame provides durability, low maintenance and corrosion resistance
- Tongue and groove section joint and bottom weather seal provide protection against the elements
- New leading-edge bulb seal provides a better section joint seal for additional protection (Amarr 3552 only)
- Heavy-duty through bolt construction
- Available in 1" width increments
- ClearView Aluminum Strut System does not restrict viewing area and adds strength and durability to doors; available up to 24' wide doors (Amarr 3552 only)
- Amarr 3552 available in odd height doors

SPECIFICATIONS

	Heavy-Duty Amarr 3552	Medium-Duty Amarr 3502
MATERIAL	Aluminum	Aluminum
CONSTRUCTION LAYERS	Single	Single
PANEL OPTIONS		
Full View	•	•
Perforated	•	
Louvered Ventilation	•	
Aluminum	•	•
Insulated Aluminum	•	
DOOR THICKNESS	2" [5.1cm]	2" [5.1cm]
MINIMUM WIDTH	2'	2'
MAXIMUM WIDTH (in 1" increments)	24' 2"	12' 2"
MINIMUM HEIGHT	6'	6'
MAXIMUM HEIGHT	20' 1"	12' 1"
SECTION HEIGHTS ¹	18", 21", 24"	21", 24"
WIND LOAD ² AVAILABLE	•	•
FINISH WARRANTY ³	5 Years	5 Years
WORKMANSHIP/HARDWARE WARRANTY ³	1 Year	1 Year

¹ For complete door height configuration chart visit amarr.com or contact your local Amarr dealer.
² It is your responsibility to make sure your garage door meets local building codes.
³ For complete warranty details, visit amarr.com or contact your local Amarr dealer.

GLAZING OPTIONS

Amarr 3502 not available in 1/4" or insulated glass.

Single Pane													Insulated	
Tempered				Lami-nated	Polycarbonate			Acrylic			Tempered			
	1/8"	1/8" Low-E	1/4"	1/4" Low-E	1/4"	Single 1/8"	Single 1/4"	Tri-Wall 5/8"	1/8"	1/4"	1/2"	1/2"	1/2" Low-E	
CLEAR	STD	•	•	•		•	•	•	•	•	•	•	•	
OBSCURE	•													
GRAY	•											•	•	
BRONZE	•							•				•	•	
GREEN	•											•	•	
FROST	•		•					•				•		
SNOW					•			•						
WHITEOUT					•									
BLACK ICE					•									


PANEL OPTIONS



ALUMINUM & INSULATED ALUMINUM



PERFORATED ALUMINUM*
0.312" square perforations on 1/2" centers
*Also available in Mill finish.



LOUVERED ALUMINUM
6 columns of (12) 3"x 3/4" vents on a 4' x 24" panel



Amarr 3552 in Clear Anodize with Clear glass

COLORS

Actual color may vary from samples shown.

In Stock

ANODIZE

Amarr 3502 available in Clear anodize only.



CLEAR (AN)



DARK BRONZE (AD)



BLACK (BA)

PAINT



WHITE Powder Coat (WH)

Special Order

ANODIZE

Longer lead time and price upcharge apply.



CHAMPAGNE (AH)



COPPER (AC)



MEDIUM BRONZE (AM)

PAINT

PVDF (Kynar®) & Powder Coat

Longer lead time and price upcharge apply.



WHITE (PVDF)



BONE WHITE



IVORY



SANDSTONE



BURNT SUN



SIERRA TAN



BEIGE



LIGHT SEAWOLF
BEIGE



DOVE GRAY



SLATE GRAY



CHARCOAL GRAY



PATINA GREEN



DARK IVY



HARTFORD
GREEN



MILITARY BLUE



INTERSTATE
BLUE



COLONIAL RED



BOYSENBERRY



SAGE BROWN



QUAKER BRONZE



SUPER BLACK




CARNIVAL RED II†



CLASSIC COPPER†



CHAMPAGNE
PEARL†



PEWTER†



SILVER†

†PVDF only.



	PVDF (Kynar®)	Powder Coat
FADE RESISTANT	++	+
CORROSION RESISTANT	++	+
UV RESISTANT	++	+
ABRASION RESISTANT	+	++
STANDARD COLORS	26	21
RAL/CUSTOM COLORS PRICE UPCHARGE	\$	\$\$
TOUCH-UP PAINT	Included	NOT included



MULTI-TENANT OFFICE BUILDING

THE MOVE OFFICE BUILDING - CASTLE ROCK, CO

CHALLENGE:

Provide multiple tenants of a four-story office building the opportunity to open up their individual interiors as well as shared spaces during the work day to take advantage of natural ventilation and surrounding scenic mountain views.

RESULTS:

An innovative, functional and safe four-sided building design feature that allows a large volume of natural airflow, maximizes the use of natural daylighting and creates virtually unobstructed views of the surrounding cityscape and rugged scenery.

Complete case study can be found at amarr.com/casestudies

Energy Efficient Polyurethane Insulated Steel Doors


High R-value doors to meet all your needs. Amarr polyurethane insulated products are constructed using CFC-free polyurethane insulation to create a strong monolithic panel. Our most energy efficient doors.



Amarr® 2743 3" SUPER-DUTY

Superior Energy Efficiency
Exceptional performance for long-term value


R-Value
28.0



Amarr® 2042 2" EXTRA HEAVY-DUTY

High Energy Efficiency
Flush modern look



R-Value
19.4



Amarr® 2742B/2742C 2" HEAVY-DUTY

High Energy Efficiency
Pencil groove design for added strength


R-Value
19.4



Amarr® 2747 1-5/8" HEAVY-DUTY

Versatile replacement section
Compatible with other manufacturer's shiplap doors

R-Value
15.1



Amarr® 2741 1-3/8" MEDIUM-DUTY

Energy efficient
Competitively priced


R-Value
14.5



Amarr® 3040 1" MEDIUM-DUTY

Energy efficient and economical
Ideally suited for vertical dock doors

R-Value
10.1





Amarr 2042 with 3 Clear Anodize Aluminum Full View sections (custom painted by owner)

Repair any 1-5/8" Shiplap Door with Amarr 2747



DAMAGED COMPETITIVE DOOR



REPAIRED DOOR WITH AMARR 2747
REPLACEMENT SECTION

- Compatible section profile
- Similar exterior and interior groove designs
- Comparable section weights requires no spring change




COMPETITOR



AMARR

Air Infiltration Performance



- Meets Building Energy Efficiency Standards:
ASHRAE 90.1
IECC® 2015
CA Title 24 2016
- 3rd party certification tested
- Certification available for
Amarr 2743, 2042, 2742, 2741 and 3040

Both seals required to meet the above standards


Energy Efficient Polyurethane Insulated Steel Doors

Amarr Polyurethane Insulated products offer the all right options to meet your customers’ needs – from an R-value of 28.0 to modern flush panel to custom colors with Amarr Color zone the possibilities are infinite.




Amarr 2742 in True White with 26"x13" windows


PANEL DESIGNS



AMARR 2042:
FLUSH PANEL



AMARR 2743, 2742, 2741 and 3040:
PENCIL GROOVED



AMARR 2747:
WIDE GROOVE


STEEL COLORS




TRUE WHITE (TW)



SANDTONE (ST)



COMMERCIAL
GRAY (CY)



COMMERCIAL
BROWN (CB)



Amarr Color Zone
More than 600 color
choices. Price upcharge
applies. See page 19.

Amarr 2042 available in True White only.

Amarr steel doors are pre-painted; for custom colors, exterior latex paint must be used. Visit amarr.com for instructions on painting. Actual paint colors may vary from samples shown.

WINDOW OPTIONS



26"x13" DOUBLE INSULATED
ACRYLIC WINDOWS
with BLACK FRAME

Not available for Amarr 2743



24"x12" TEMPERED
INSULATED GLASS with
BLACK or WHITE FRAME

Not available for Amarr 2747 & 3040



24"x8" TEMPERED INSULATED
with BLACK FRAME

Not available for Amarr 3040



24"x6" DOUBLE INSULATED
ACRYLIC WINDOWS
with BLACK FRAME

Not available for
Amarr 2743, 2747 & 3040

SPECIFICATIONS

	Super-Duty Amarr 2743	Extra Heavy-Duty Amarr 2042	Heavy-Duty 2742B 2742C		Heavy-Duty Amarr 2747	Medium-Duty Amarr 2741	Medium-Duty Amarr 3040
DOOR THICKNESS	3" [7.6 cm]	2" [5.1cm]	2" [5.1cm]		1-5/8" [4.1cm]	1-3/8" [3.5cm]	1" [2.5cm]
PROFILE DESIGN	Tongue and Groove	Tongue and Groove	Tongue and Groove		Shiplap	Tongue and Groove	Tongue and Groove
EXTERIOR STEEL THICKNESS	27 ga	20 ga	27 ga		27 ga	27 ga	.012"
PANEL DESIGN	Pencil Groove	Flush	Pencil Groove		Wide Groove	Pencil Groove	Pencil Groove
STEEL EMBOSSEMENT	Stucco	Stucco	Stucco		Stucco	Stucco	Stucco
CONSTRUCTION LAYERS	Triple	Triple	Triple		Triple	Triple	Triple
INSULATION ¹	Polyurethane	Polyurethane	Polyurethane		Polyurethane	Polyurethane	Polyurethane
R-VALUE ²	28.0	19.4	19.4		15.1	14.5	10.1
HINGE REINFORCEMENT	Continuous Strip	Continuous Strip	Backer Plate	Continuous Strip	Continuous Strip	Backer Plate	Backer Plate
BOTTOM WEATHER SEAL (Co-Extruded PVC)	Triple Contact	Dual Contact	Dual Contact		Triple Contact	Dual Contact	Dual Contact
DOOR WIDTH MIN	5'	5'	5'		5'	5'	5'
DOOR WIDTH MAX	40' 2"	40' 2"	40' 2"		24' 2"	20' 2"	20' 2"
DOOR HEIGHT MIN	7'	7'	7'		7'	7'	7'
DOOR HEIGHT MAX	26' 1"	26' 1"	26' 1"		26' 1"	14' 1"	16' 1"
PASS DOOR		•	•				
ALUMINUM SECTIONS		•	•				
WIND LOAD ³ AVAILABLE	•	•	•			•	
PAINT FINISH WARRANTY ⁴	10 Years	10 Years	10 Years		10 Years	10 Years	10 Years
WORKMANSHIP/HARDWARE WARRANTY ⁴	1 Year	1 Year	1 Year		1 Year	1 Year	1 Year



¹ Insulation has passed self-ignition, flamespread and smoke developed index fire testing.
² Amarr 2741 calculated door section R-value is in accordance with DASMA TDS-163.
Amarr 2042 and 2742 R-value tested and verified in accordance to ASTM 518 by an independent lab.
³ It is your responsibility to make sure your garage door meets local building codes.
⁴ For complete warranty details, visit amarr.com or contact your local Amarr dealer.
* Available door width and height depends on total door weight. Total door weight cannot exceed 635 lbs for 2" track or 2200 lbs for 3" track.



Amarr 2742 in Commercial Gray with 2 Clear Anodize Aluminum Full View sections

Amarr 2042 and 2742 Options

ALUMINUM SECTION



GLAZED ALUMINUM



PERFORATED ALUMINUM†
0.312" square perforations on 1/2" centers



LOUVERED ALUMINUM
6 columns of (12) 3"x3/4" vents
on a 4'x24" panel



CLEAR
ANODIZE



DARK BRONZE
ANODIZE



BLACK
ANODIZE



WHITE
POWDER COAT

Actual color may vary
from samples

SUPERFLEX SECTION OPTION



FLEXIBLE IMPACT SECTION
see page 16 for more information.

PASS DOOR with stainless steel frame



AVAILABLE IN DOOR SIZES UP TO 16'2" WIDE X 16' TALL.
Wind load option not available.



EXTENSIVE FIRE STATION REMODEL FEATURES COMBINATION STEEL AND FULL VIEW PANEL SECTIONAL DOORS THAT PROVIDE IMPROVED VIEWS AND HIGH R-VALUE

CHALLENGE:

Replace several 25-year-old, non-insulated fire station sectional doors with high R-value doors that complement a specific exterior renovation paint scheme and allow improved views of all activity in front of and behind the station.

RESULTS:

A dramatic improvement in natural light penetration, unobstructed views through the doors from inside the fire station as well as lower heating costs due to the high 19.4 R-value of each sectional door.

Complete case study can be found at amarr.com/casestudies

Polystyrene Insulated Steel Doors

R-Value
9.4

Amarr 2432

Heavy-Duty, 2" 24-gauge steel

R-Value
9.4

Amarr 2732

Medium-Duty, 2" 27-gauge steel

Amarr 2" polystyrene insulated doors feature two solid steel skins and an advanced 4-step insulation system making these doors strong and durable.

The Amarr 2432 has a heavy-duty 24-gauge steel exterior featuring a stucco embossment with shallow pencil grooves. The Amarr 2732 exterior is made from 27-gauge steel with the same panel design and embossment.



Amarr 2432 in White with 24" x 6" windows

CONSTRUCTION

TRIPLE-LAYER Steel + Insulation + Steel



Amarr 2432



Amarr 2732

- R-Value: 9.4
- Heavy-duty hardware for smooth operation, long life and low maintenance
- Stucco embossed interior surface camouflages day-to-day wear and tear
- CFC-free polystyrene insulation is eco-friendly and chemically bonded to the steel panels building strength and energy efficiency

SPECIFICATIONS


	Heavy-Duty Amarr 2432	Medium-Duty Amarr 2732
STEEL THICKNESS (Exterior/Interior)	24 ga / 27 ga	27 ga / 27 ga
PANEL DESIGN	Pencil Groove	Pencil Groove
STEEL EMBOSSMENT	Stucco	Stucco
DOOR THICKNESS	2" (5.1cm)	2" (5.1cm)
CONSTRUCTION LAYERS	Triple	Triple
INSULATION ¹	Polystyrene	Polystyrene
R-VALUE ²	9.4	9.4
AIR INFILTRATION	.18 cfm/ft2 @ 15 mph / .30 cfm/ft2 @ 25 mph	.18 cfm/ft2 @ 15 mph / .30 cfm/ft2 @ 25 mph
MINIMUM WIDTH	6'	6'
MAXIMUM WIDTH	24' 2"	24' 2"
MINIMUM HEIGHT	7'	7'
MAXIMUM HEIGHT	26' 1"	26' 1"
WIND LOAD ³ AVAILABLE	•	•
PAINT FINISH WARRANTY ⁴	10 Years	10 Years
WORKMANSHIP/HARDWARE WARRANTY ⁴	1 Year	1 Year



See page 17 for details.

¹ Insulation has passed self-ignition, flamespread and smoke developed index fire testing.
² Calculated door section R-value is in accordance with DASMA TDS-163.
³ It is your responsibility to make sure your garage door meets local building codes.
⁴ For complete warranty details, visit amarr.com or contact your local Amarr dealer.

PANEL DESIGN



PENCIL GROOVE
WITH STUCCO EMBOSSMENT

SUPERFLEX SECTION OPTION



FLEXIBLE IMPACT SECTION - see page 16 for more information.

COLORS



TRUE WHITE (TW)



SANDTONE (ST)



COMMERCIAL
GRAY (CY)



COMMERCIAL
BROWN (CB)



More than 600 color choices. Price upcharge applies. See page 19.

WINDOW OPTIONS



24" X 12" TEMPERED INSULATED GLASS
Available with either a black or white frame.



24" x 6" DOUBLE INSULATED ACRYLIC
Available with black frame.

Medium-Duty Polystyrene Insulated Steel Doors

R-Value
6.7

Amarr 2731

Medium-Duty, 1-3/8" 27-gauge steel

Solid commercial construction meets variety and style. The Amarr 2731 is built with two 27-gauge steel layers surrounding a 1-3/8" polystyrene core. For style, the exterior layer features a flush profile with woodgrain embossment for a more upscale look reminiscent of typical residential doors. The interior skin features a flush profile with stucco embossment for a clean interior surface.



Amarr 2731 in Wicker Tan with 41"x13" windows

CONSTRUCTION

TRIPLE-LAYER Steel + Insulation + Steel



- R-Value: 6.7
- Four-step insulation system provides protection from the elements with tongue and groove construction, insulation, weather-stripping and a thermal break
- CFC-free polystyrene insulation is eco-friendly and chemically bonded to the steel panels building strength and energy efficiency

SPECIFICATIONS

	Medium-Duty Amarr 2731
STEEL THICKNESS (Exterior/Interior)	27 ga / 27 ga
PANEL DESIGN	Flush
STEEL EMBOSSMENT	Woodgrain
DOOR THICKNESS	1-3/8" (3.5cm)
CONSTRUCTION LAYERS	Triple
INSULATION ¹	Polystyrene
R-VALUE ²	6.7
MINIMUM WIDTH	6'
MAXIMUM WIDTH	18' 2"
MINIMUM HEIGHT	7'
MAXIMUM HEIGHT	14' 1"
WIND LOAD ³ AVAILABLE	•
PAINT FINISH WARRANTY ⁴	10 Years
WORKMANSHIP/HARDWARE WARRANTY ⁴	1 Year



See page 15 for details.

¹ Insulation has passed self-ignition, flamespread and smoke developed index fire testing.
² Calculated door section R-value.
³ It is your responsibility to make sure your garage door meets local building codes.
⁴ For complete warranty details, visit amarr.com or contact your local Amarr dealer.

PANEL DESIGN



FLUSH PANEL
WITH WOODGRAIN EMBOSSMENT

COLORS



TRUE WHITE (TW)



ALMOND (AL)



WICKER TAN (WK)



SANTONE (ST)



More than 600 color choices. Price upcharge applies. See page 19.

WINDOW OPTIONS



21" x 13" SHORT PANEL*



41" x 13" LONG PANEL*



24" x 6" DOUBLE INSULATED ACRYLIC
Available with black frame.

* True White shown; also available in Almond, Wicker Tan, and Sandtone.
Available with Clear, Obscure, or Insulated glass.

Ribbed Panel Steel Doors

R-Value
7.0

Amarr 2002, 2012, 2022
Extra Heavy-Duty, 20-gauge steel

R-Value
7.0

Amarr 2402, 2412, 2422
Heavy-Duty, 24-gauge steel

R-Value
7.0

Amarr 2502, 2512, 2522
Medium-Duty, nominal 24-gauge steel

Amarr 2" ribbed panel steel doors, insulated and non-insulated, are the industry workhorses and our most versatile doors. Choose from extra heavy-duty 20-gauge, heavy-duty 24-gauge and medium-duty nominal 24-gauge steel. From manufacturing plant to auto dealerships, these doors keep working wherever they are installed.




CONSTRUCTION

SINGLE-LAYER Steel



Amarr 2002/2402/2502

DOUBLE-LAYER Steel + Insulation



Amarr 2012/2412/2512

TRIPLE-LAYER Steel + Insulation + Steel



Amarr 2022/2422/2522

- Deeply ribbed panel with a smooth texture
- Can be field-modified with CFC-free polystyrene insulation with a nylon or steel backer
- Tongue and groove construction with three positive points of contact provides a more efficient barrier against moisture and air infiltration
- U-shaped vinyl bottom weather seal in a full-length PVC retainer effectively keeps out the elements

SPECIFICATIONS

	Extra Heavy-Duty			Heavy-Duty			Medium-Duty		
	Amarr 2002	Amarr 2012	Amarr 2022	Amarr 2402	Amarr 2412	Amarr 2422	Amarr 2502	Amarr 2512	Amarr 2522
STEEL THICKNESS (Exterior/Interior)	20 ga	20 ga	20 ga / 25 ga	24 ga	24 ga	24 ga / 25 ga	Nominal 24 ga	Nominal 24 ga	Nominal 24 ga / 25 ga
PANEL DESIGN	Deep Ribbed	Deep Ribbed	Deep Ribbed	Deep Ribbed	Deep Ribbed	Deep Ribbed	Deep Ribbed	Deep Ribbed	Deep Ribbed
STEEL EMBOSSEMENT	Smooth	Smooth	Smooth	Smooth	Smooth	Smooth	Smooth	Smooth	Smooth
DOOR THICKNESS	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)
CONSTRUCTION LAYERS	Single	Double	Triple	Single	Double	Triple	Single	Double	Triple
INSULATION ¹		Polystyrene	Polystyrene		Polystyrene	Polystyrene		Polystyrene	Polystyrene
R-VALUE ²		7.0	7.0		7.0	7.0		7.0	7.0
MINIMUM WIDTH	6'	6'	6'	6'	6'	6'	6'	6'	6'
MAXIMUM WIDTH	26' 2"	26' 2"	26' 2"	30' 2"	30' 2"	30' 2"	20' 2"	20' 2"	20' 2"
MINIMUM HEIGHT	7'	7'	7'	7'	7'	7'	7'	7'	7'
MAXIMUM HEIGHT	26' 1"	26' 1"	26' 1"	26' 1"	26' 1"	26' 1"	14' 1"	14' 1"	14' 1"
WIND LOAD ³ AVAILABLE	•	•	•	•	•	•	•	•	•
PAINT FINISH WARRANTY ⁴	10 Years	10 Years	10 Years	10 Years	10 Years	10 Years	10 Years	10 Years	10 Years
WORKMANSHIP/HARDWARE WARRANTY ⁴	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year



¹ Insulation has passed self-ignition, flamespread and smoke developed index fire testing.

² Calculated door section R-value.

³ It is your responsibility to make sure your garage door meets local building codes.

⁴ For complete warranty details, visit amarr.com or contact your local Amarr dealer.

See page 17 for details.



Amarr 2412 in Commercial White with 24" x 6" windows

PANEL DESIGN



RIBBED PANEL

SUPERFLEX SECTION OPTION



FLEXIBLE IMPACT SECTION – see page 16 for more information.

STEEL COLORS



COMMERCIAL
WHITE (WH)



COMMERCIAL
GRAY (CY)
2402/2412/2422 only



COMMERCIAL
BROWN (CB)
2402/2412/2422 only



COMMERCIAL
BLACK (BG)*
2402/2412/2422 only

*Price upcharge applies.



Amarr® Color Zone

More than 600 color
choices. Price upcharge
applies. See page 19.

Amarr steel doors are pre-painted; for custom colors, exterior latex paint must be used.
Visit amarr.com for instructions on painting. Actual paint colors may vary from samples shown.

WINDOW OPTIONS

Available with either a black or white frame.



24" X 12" SINGLE PLEXIGLAS®
24" X 12" INSULATED PLEXIGLAS®



24" X 6" DSB or PLEXIGLAS®

ALUMINUM SECTION OPTIONS



GLAZED ALUMINUM



PERFORATED ALUMINUM†
0.312" square perforations on ½" centers



LOUVERED ALUMINUM
6 columns of 12) 3"x 3/4" vents on a 4' x 24" panel



CLEAR ANODIZE



DARK BRONZE
ANODIZE



BLACK ANODIZE



WHITE
POWDER COAT

Actual color may vary from samples shown.
See page 5 for additional finish options.

†Also available in Mill finish.



Amarr 2512 in Commercial White with 2 White Aluminum Full View sections

Amarr SuperFlex

Flexible Impact Sections

Amarr SuperFlex impact resistant sections are the answer to lower door section damage common in today's busy warehouses.

CONSTRUCTION

- High-performance Thermoplastic Polyolefin (TPO) interior and exterior polymer skin
- Flexible fiberglass tube frame with steel corner brackets
- Insulated 1-3/4" thick section with an 8.5 R-value

FEATURES

- Flexes in and out an average of 8"–10"
- Suitable for environmental temperatures from 20°F to 131°F (-7°C to 54°C)
- Retrofits to most 1-1/2" – 2" thick sectional doors
- Provides an exceptional thermal seal

BENEFITS

- Reduced lower door section damage
- Reduced maintenance costs
- Excellent UV resistance
- Outstanding chemical resistance
- Seals against tongue & groove or shiplap door sections

SIZE AVAILABILITY

- Section heights: 18", 21" and 24"
- Section widths: 8'2", 9'2", 10'2" and 12'2" (custom widths available up to 12'2")

DOOR AVAILABILITY

- One- or two-section configurations
- Polyurethane Insulated – Amarr 2042 and 2742
- Polystyrene Insulated – Amarr 2432 and 2732
- Ribbed Panel – all models



Unique construction of the Amarr SuperFlex section allows it to flex; providing durability and reliable operations.



Amarr SuperFlex sections flex upon impact and return to normal operating position.



High impact polymer skin deflects minor blows from forks.

Amarr Wind Load Rated Commercial Doors

When installed according to our instructions and local building codes, Amarr hurricane rated doors:

- Withstand rapid cyclic pressure and static load forces up to 240 mph.¹
- Resist large missile impact at 50' per second (35 mph).²

¹ Exposure B with a mean roof height less than 30' based on ASCE7-10, (57/-67 PSF)

² Option available on select models only.

Amarr wind load rated doors meet or exceed these building codes:

- Florida Building Code (FBC)
- International Code Council (ICC)
- Texas Department of Insurance (TDI)
- High-Velocity Hurricane Zone (HVHZ) (Miami – Dade and Broward Counties)

Track Lift Options


Track lift types vary based on the amount of vertical space or

headroom available above the door.

2" or 3" track for these lift applications


is available. Custom track

configurations are also available.




STANDARD LIFT

2" TRACK
Headroom = 12-3/4"
15" Radius = 15-1/2"
Sideroom = 5"
3" TRACK
Headroom = 16-7/8"
Sideroom = 5-1/2"




LOW HEADROOM REAR

2" TRACK
Headroom = 6-1/2"
Sideroom = 5"
3" TRACK
Headroom = 7-5/8"
Sideroom = 5-1/2"



FOLLOW THE ROOF PITCH

2" TRACK
Headroom = 12-3/4"
15" Radius = 15-1/2"
Sideroom = 5"
3" TRACK
Headroom = 16-7/8"
Sideroom = 5-1/2"



LOW HEADROOM FRONT

2" TRACK
Headroom = 12-13/16"
Sideroom = 5"
3" TRACK
Headroom = 16-7/8"
Sideroom = 5-1/2"

Amarr




RAPID INSTALL VERTICAL LIFT

- Available for all commercial steel sectional doors
- Designed for commercial warehouse and dock doors sizes up to 9'4" x 10'
- Only 14 wall anchor attachments for a 10' tall door
- A one-piece .063 heavy-gauge vertical track
- Preinstalled integrated end bearing plate
- Select wind load approvals
- Saves approximately 20 minutes of installation time
- Available on most wind load doors up to 9'4" x 10" as a track only option


2" TRACK
Headroom = Door Height +13"
Sideroom = 5"

3" TRACK
Headroom = Door Height +13"
Sideroom = 5-1/2"



VERTICAL LIFT

2" TRACK
Headroom = Door Height +13"
Sideroom = 5"
3" TRACK
Headroom = Door Height +13"
Sideroom = 5-1/2"



HIGH LIFT

2" TRACK
Headroom = 12-1/2"
Sideroom = 5"
3" TRACK
Headroom = 13-1/2"
Sideroom = 5-1/2"

Product Specifications

AMARR COMMERCIAL SECTIONAL DOORS

SECTIONAL ALUMINUM MULTIVIEW	FULL VIEW		ENERGY EFFICIENT POLYURETHANE							
	Modern	Heavy-Duty	Medium-Duty	Super-Duty	Extra Heavy-Duty	Heavy-Duty		Heavy-Duty	Medium-Duty	Medium-Duty
	3582	3552	3502	2743	2042	2742B	2742C	2747	2741	3040

EXTERIOR PANEL DESIGN										
Flush					•					
Deep Ribbed										
Pencil Groove				•		•	•		•	•
Wide Groove								•		
Stile and Rail	•	•	•							
Aluminum Sections	•	•	•		•	•	•			
EXTERIOR PANEL TEXTURE										
Smooth	•	•	•							
Stucco Embossment				•	•	•	•	•	•	•
Woodgrain Embossment										
INTERIOR PANEL TEXTURE										
Smooth										
Stucco Embossment				•	•	•	•	•	•	•
CONSTRUCTION LAYERS										
Steel + Insulation + Steel				•	•	•	•	•	•	•
Steel + Insulation										
Steel										
Extruded Aluminum	•	•	•							
MINIMUM STANDARD WIDTH	2'0"	2'0"	2'0"	5'0"	5'0"	5'0"	5'0"	5'0"	5'0"	5'0"
MAXIMUM STANDARD WIDTH	20'2"	24'2"	12'2"	40'2"	40'2"	40'2"	40'2"	24'2"	20'2"	20'2"
MAXIMUM STANDARD HEIGHT	20'1"	20'1"	12'1"	26'1"	26'1"	26'1"	26'1"	26'1"	14'1"	16'1"
DOOR THICKNESS	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	3" (7.6cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	1-5/8" (4.1cm)	1-3/8" (3.5cm)	1" (2.5cm)
INSULATION ¹				Polyurethane	Polyurethane	Polyurethane	Polyurethane	Polyurethane	Polyurethane	Polyurethane
R-VALUE				28.0 ³	19.4 ²	19.4 ²	19.4 ²	15.1 ³	14.5 ³	10.1 ³
EXTERIOR STEEL THICKNESS				27 ga	20 ga	27 ga	27 ga	27 ga	27 ga	.012"
END STILE				16 ga	20 ga (16 ga optional)	20 ga (16 ga optional)	20 ga (16 ga optional)	16 ga	20 ga	20 ga
CENTER STILE										
HINGE REINFORCEMENT				20 ga continuous strip	20 ga continuous strip	20 ga backer plate	20 ga continuous strip	20 ga continuous strip	20 ga backer plate	20 ga backer plate
BOTTOM WEATHER SEAL										
Aluminum Retainer	•	•	•							
Co-Extruded PVC				Triple Contact	Dual Contact	Dual Contact	Dual Contact	Triple Contact	Dual Contact	Dual Contact
WINDOW OPTIONS										
24" x 6"					•	•	•		•	
24" x 8"				•	•	•	•	•	•	
24" x 12"				•	•	•	•		•	
26" x 13"					•	•	•	•	•	•
21" x 13"										
41" x 13"										
PASS DOOR					•	•	•			
STEEL EXTERIOR COLOR OPTIONS										
True White (TW) /Commercial White (WH)				TW	TW	TW	TW	TW	TW	TW
Almond (AL)										
Wicker Tan (WK)										
Sandtone (ST)				•		•	•	•	•	•
Commercial Gray (CY)				•		•	•	•	•	•
Commercial Brown (CB)				•		•	•	•	•	•
Commercial Black (BG) [†]										
Amarr Color Zone [‡]				•	•	•	•	•	•	•
HIGH CYCLE SPRINGS TO 100K	•	•	•	•	•	•	•	•	•	•
WIND LOAD AVAILABLE ⁴		•	•	•	•	•	•		•	
WARRANTY ⁵										
Paint Finish	5 Years ⁶	5 Years ⁶	5 Years ⁶	10 Years	10 Years	10 Years	10 Years	10 Years	10 Years	10 Years
Workmanship/Hardware	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year

¹ Insulation has passed self-ignition, flamespread and smoke developed index fire testing.
² Amarr 2042 and 2742 R-value tested and verified in accordance to ASTM 518 by an independent lab.
³ Calculated door section R-value.
⁴ It is your responsibility to make sure your garage door meets local building codes.
⁵ For complete warranty details, visit amarr.com or contact your local Amarr dealer.
⁶ PVDF (Kynar) and powder coat finish warranty.

* Available door width and height depends on total door weight.
Total door weight cannot exceed 635 lbs for 2" track or 2200 lbs for 3" track.
[†] Price upcharge applies.



Amarr Rapid Install
Available for all commercial steel sectional doors.
See page 17 for more information.

Amarr Color Zone[†]
 More than 600 Sherwin-Williams SnapDry™ paint colors.
 The approved list can be found at amarr.com/amarr_color_zone
 SnapDry paint is resistant to dirt, fingerprints and UV weathering.
 Your local Sherwin-Williams store can provide SnapDry paint chips.




Amarr 3552 in Clear Anodize with Clear glass

OTHER COMMERCIAL MODELS AVAILABLE



Rolling Slat



Rolling Sheet

Our Philosophy. Since 1951, we have successfully raised the standards of quality, value, and dependability in the garage door industry. Today, with the same promise of individual attention and great value for all our customers, we remain committed to offering Amarr products and services that raise those standards even higher.

Your Local Amarr Dealer:

Entrematic
165 Carriage Court
Winston-Salem, NC 27105
800.503.DOOR
www.amarr.com



Entrematic and Amarr as words and logos are trademarks owned by Entrematic Group AB or companies within the Entrematic Group.

Door specifications and technical data subject to change without notice.

Entrematic products may be the subject of one or more U.S. and/or foreign, issued and/or pending, design and/or utility patents.

©Entrematic Group AB 2019. All rights reserved.
Printed in USA Form #6300819/10M/GVS

ENTRE/MATIC

